

Entry Projector

PJ WXC1110

RICOH
imagine. change.



A quality projector that fits in your pocket.

When you need a projector that's as mobile, versatile and as flexible as you are, this device is the answer. Easy to carry and enabling you to project almost anywhere when you're on the move, it's ideal for media and presentations in offices and classrooms, so you can always get your message across. It's quick to set up and easy to use, and of course, you'll get supreme reliability and all the innovations you need to make your presentations shine.

- LED projection with 20,000 hours' life (in bright mode) – no need for lamp replacement so it's low maintenance.
- Short-throw projection – throw ratio 0.8 - that's perfect for small spaces, classrooms/meeting rooms as well as for use on general-sized screens.
- Very compact in size, superlight in weight and can be carried anywhere.
- 600lm brightness and clear image for its size.
- Perfect for being on the move, thanks to its battery attachment option.



Small size. Big impact.

Presentations made seamless.

This new model has been designed with mobile working in mind. And because it's so light and so compact, your presentations and projections can go wherever you go. So if you need to move from place to place internally, or you're a specialist that's always out of the office, this is the projector to support your more joined-up work-life.




Power up. When the power's down.

The extra-long life LED bulb, which means you don't have to change the lamp, is one innovation. The short throw projection, reliability and 600lm in such a compact device are three others. But what's really impressive is the versatility of its power options. Ideal for areas where the main power supply is unstable or non-existent, there's a battery back-up with means you can keep on presenting where other projectors would stop.



Get connected. Wherever you are.

No matter if you're an expert at presentations, or just starting out, this projector makes everything easy for you. Quick to set up, its easy-to-use interface means you can concentrate on what's important, and let us look after the technology. And the connectivity options – including WiFi/WLAN through the optional EZCast Pro dongle – mean you can project or present almost anywhere.



PJ WXC1110

MAIN SPECIFICATIONS

GENERAL

Projection system:	0.45" WXGA DMD Chip
Resolution:	1,024,000 pixels (1,280 x 800)
Panel:	Panel size: 0.45 inch Aspect ratio: 16:10
Brightness:	600 lumen
Colour reproducibility:	16,700,000 colours
Contrast ratio:	600:1
High contrast ratio:	40,000:1
Projection screen size:	25" to 200"
Projection distance:	0.43-3.44 m (from projection window to the screen)
Light source:	RGB LED
LED life:	Bright mode: 20,000 hours Eco mode: 30,000 hours
RGB compatible signals :	Real display: WXGA (1,280 x 800), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480) Compressed representation: UXGA (1,600 x 1,200), SXGA (1,280 x 1,024)
Input signals:	NTSC, PAL, SECAM, NTSC4.43, PAL-M, PAL-60, 50 Hz (mono), 60 Hz (mono)
Analogue RGB compatible scanning frequency:	Horizontal: 15 - 91 kHz Vertical: 24 - 120 Hz, 120 Hz for 3D mode
Focus:	Manual
Connection terminal:	Mini D-SUB15pin x 1 (Computer IN) , HDMI x 1, TYPE-A x 1 (USB), Wired in/out (3.5 mm phone jack) x 1
Wireless LAN:	LAN IEEE 802.11b/g/n compliant
Primary features:	Mute (Blank), Re-size (Magnify), Auto keystone, Password protection, User logo, Eco mode, 3D ready, Wall Color mode, Kensington lock, Firmware update
Built-in speaker:	1.5 W mono
Dimensions (W x D x H):	112.5 x 50.5 x 105 mm
Weight:	0.45 kg
Power source:	100 - 240 V +/-10%, 50/60 Hz

ECOLOGY

Power consumption:	Operating power: 76 W Stand-by mode: 0.5 W
Operating temperature:	5°C - 40°C
Operating humidity:	80%
Noise level:	Standard mode: 34 dB Eco Mode: 24 dB

ACCESSORIES

Read this first / Manual (Starting Guide), RGB cable, CD-ROM and manual, Remote control with batteries, AC adapter, Carrying bag, Lens cap

For availability of models, options and software, please consult your local supplier.

ISO9001 certified, ISO14001 certified, ISO27001 certified

All brand and/or product names are trademarks of their respective owners.

Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2016 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.

RICOH
imagine. change.

www.ricoh-europe.com